

# Sutper®TPE E1010002

## Product Description

A soft, colorable SEBS-based thermoplastic elastomer (TPE) compound. The product has uniform particle size and is free of impurities, offering excellent physical properties and chemical resistance.

## Specifications

Applications	•Extrusion Molding Sealing strip
Environmental	•RoHS compliant
Appearance	•Natural color
Form	•Granules
Molding method	•Extrusion Molding
Availability	•Europe •North America •Asia •Africa & Middle East

Physical Properties	Typical Value	Unit	Test Method
Density	0.99	g/cm <sup>3</sup>	ASTM D792
Melt Flow Index (190°C*5kg)	13	g/10min	ASTM D1238

Hardness	Typical Value	Unit	Test Method
Shore D,3sec,23°C	47	D	ASTM D2240

Mechanical Properties	Typical Value	Unit	Test Method
100% Tensile Strength - Vertical Flow (23°C)	8.0	Mpa	ASTM D412
Tensile Strength - Vertical Flow (23°C)	26	Mpa	ASTM D412
Break Elongation-Vertical Flow 23°C	600	%	ASTM D412
Tear Strength -Vertical Flow 23°C Die C	65	KN/m	ASTM D624

## Additional Information

- The above test data were obtained using fan gate injection molded specimens with dimensions of 110 mm × 80 mm × 2 mm. The tensile strength, elongation at break, and stress at a given elongation were tested perpendicular to the flow direction, while tear strength was tested along the flow direction.
- The properties listed are typical and should not be considered technical specifications or part of an agreement.
- The user should be aware that Sutper needs to confirm all final details before taking any action based on the information and recommendations in this document.